

9th NASA Space Exploration and Space Weather Workshop

Joseph C. Hunt Jr.
Spitzer Deputy Mission Manager / Flight Director

September 26, 2017

Jet Propulsion Laboratory California Institute of Technology 4800 Oak Grove Drive Pasadena, CA 91109-8099 USA



Agenda


- Mission Overview
- Space Weather Monitor Sources
- Operational Space Weather Process
- Summary of Key Events
- Summary



Mission Overview


Salient Features

- Class: BCategory: 2
- Heliocentric orbit trailing the Earth
- 85 cm Beryllium telescope operating at 26K
- 2 arrays with 3-5 micron wavelength coverage
- Launch: 25 Aug 2003, Warm Mission: 27 July 2009
- Beyond Mission: 1 Oct 2016 31 March 2019
- 100% community observatory




Science

- To study the properties of extrasolar planets and search for super-earths around nearby solar-type stars.
- To study galaxies as they were when the Universe was less than 1 Gyr old, and to understand how galaxies and clusters of galaxies have evolved with cosmic time.
- To complete the census of the Galaxy for young stars, star forming regions and dusty post-main sequence stars, and search for new classes of brown dwarfs and super-planets.
- To determine the cosmic distance scale in the local Universe with unprecedented precision by the first systematic application of mid-infrared observations to this critical problem.






Mission Phases





Spitzer's Orbit



Spitzer follows the Earth around the Sun. Its orbit is slightly more elliptical than the Earth's and it slowly recedes from Earth at about 0.1 AU/yr.



Ground Segment Requirement

Launch and Cryo Mission Phase

Space Weather event producing protons exceeding the 100 MeV energy level and particle flux greater than 100 pfu

- The Ground Segment, using both local and telemetry information, shall decide the time at which the Observatory is to resume science operations after a solar flare
 - real-time or stored sequence commands to accomplish this.
- The Ground Segment shall recognize and respond to a solar flare event within 12 hours of occurrence
 - powering off unprotected science loads as necessary to minimize radiation effects.

Warm/Beyond Mission Phases

- Monitor and annotate for S/C and science performance impacts or degradation.
 - ground operation provide notification



Space Weather Monitor Sources

GSFC SWRC-Space-Weather-Research-Center

- SWRC Alerts
- SWRC Model with Spitzer's coordinates
- SWRC Summary Reports

NOAA GOES

After more than twelve years of drifting away from the Earth, Spitzer's distance from Earth is ~1.38 AU, and the GOES satellites no longer serve as a predictive tool for the S/C however, may provide ground transmission possible impacts.

STEREO A/B

 During Spitzer's prime mission phase, STEREO-B and Spitzer shared the same heliocentric Right Ascension, no longer applicable. STEREO-A is approaching in right Ascension and could provided useful data to support alerts.

SPITZER


 Mass Memory Card, Power Subsystem, Star Tracker, and IRAC instrument have proven to exhibit behavior that directly correlates to space weather events.



Mass Memory Card (MMC) Soft Scrub Errors

The EDAC continues to correct for single bit errors due to background radiation. The corrections are summed by the ratio of corrupted bits over time.


Increased background "noise" and the rapid changes in soft scrub error rates are indicative of space weather events.





Power/Solar Array Panel

Continuous trending provides performance statics for the output power.




Major solar weather events in October-November 2003 and January 2005 reduced the solar panel assembly output by 4.7% and 2.8%, respectively. In addition, in early November 2010, a micrometeoroid impact damaged one of the solar panel assembly's strings, reducing the total power output by an additional 6.5%. The solar panel still operates well within the power output margin.



Star Tracker

STA component-level fault protection utilizes a series of checks to test the component health. Values are set to monitor counters for fault persistence





The accumulated and cumulative counts increased resetting the STA. This correlated with the May 2012 space weather event.



Infrared Array Camera (IRAC) Radhits


Based on the instrument exposure time the nominal observed Radhits are 4 per second with very little scatter.







Space Weather Process





Collaborative HTML Page

llem	Title	Message ID	Activity ID	Class	Edge Time	Alarms	MMC Soft Scrub Errors	Star Tracker	Power	IRAC
1	SWE_2017-09-18_ 262	20170918-AL-003	2017-09-17T14:24:00-CME-001	O	262 / 0220	No	Nominal			
			2017-09-17T12:09:00-CME-001	С						
2	SWE_2017-09-17_ 263	20170917-AL-004	2017-09-17T12:09:00-CME-001	0	263 / 000	No	Nominal	No	No	No
3	SWE_2017-07-28_ 212	20170728-AL-002	2017-07-28T05:36:00-CME-001	С	212 / 01621	No	Nominal	No	No	Small
4	SWE_2017-06-29_ 183	20170629-AL-001	2017-06-28T16:24:00-CME-001	S	183 / 0120	No	Nominal	No	No	Small
			2017-06-28T15:24:00-CME-001	8						
5	SWE_2017-04-19_ 111	20170419-AL-003	2017-04-18T19:48:00-CME-001	С	111 / 0226	No	Nominal	No	No	No
6	SWE_2017-01-03_006	20170103-AL-001	2017-01-03T03:12:00-CME-001	С	6 / 0731	No	Nominal	No	No	No
8										
9										
10										
11										
12										
13										
14										
15										
16										
17										



Summary of Key Events to Date






Table of Key Events

INPUT	IMPACT RESULTS							
Title	ММС	Star Tracker	Power	IRAC				
WAM_2003-1029_302	Board 0 & 1 SSE	Noise + WASS Errs	SA pwr degraded	Increased Noise				
WAM_2003-1103_307	Board 0 & 1 SSE	Noise + WASS Errs	SA pwr degraded	Commanded Off				
WAM_2004-1018_292	Board 0 & 1 SSE	No	No	No				
WAM_2005-1020_020	Board 0 & 1 SSE	No	No (CTA temp inc)	(IRS – Inc. Noise)				
WAM_2005-0926_269	Board 0 & 1 SSE	No	No	No				
WAM_2006-1213_347	Board 0 & 1 SSE	No	No (CTA temp inc)	Commanded Off				
WAM_2007-0818_230	Board 1 SSE	No	No	No				
NSE_2012-0215_044	Board 1 SSE	No	No	No				
SWE_2012-0307_067	Board 0 & 1 SSE	No	No	Lost Science Data				
SWE_2012-0512_133	Board 0 SSE	No	No	No				
NSE_2012-0624_176	No	No	No	Increased Noise				
NSE_2013-0201_041	Masked by IDIO	Dropped Acq	No	Increased Noise				
SWE_2014-0223_054	Board 0 & 1 SSE	No	No	Increased Noise				



Summary

• The Observatory remains in excellent health

Spitzer continues to deliver outstanding science.

- Mission Operations continues to utilize SWRC services
 - Feedback from Ops teams is the visualization model with the S/C embedded is useful

- Collaboration of user community for space weather events via "DONKI"
 - ➤ How do we manage NASA's missions proprietary data ?

- Possible enhancements:
 - Life cycle chart of solar progression vs selected events



Acknowledgement

Thanks to Goddard's SWRC for continued services which has provided outstanding support to the interplanetary user community.

A large number of people from the Spitzer project, support organizations at the Jet Propulsion Laboratory, Lockheed Martin Space System Company, and the Spitzer Science Center at the California Institute of Technology contributed to the operations described herein.



Backup Material

Instruments

- Three science instruments
 - ➤ IRAC Infrared Array Camera
 - \circ Bands: 3.6 μm, 4.5 μm, 5.8 μm, and 8.0 μm
 - ➤ MIPS Multi-band Imaging Photometer
 - O Bands: 24 μm, 70 μm, and 160 μm
 - > IRS Infrared Spectrometer
 - O Bands: $5.2 \,\mu\text{m} 14.5 \,\mu\text{m}$, $9.9 \,\mu\text{m} 19.6 \,\mu\text{m}$, $14.0 \,\mu\text{m} 38.0 \,\mu\text{m}$, and $18.7 \,\mu\text{m} 37.2 \,\mu\text{m}$
- In the Cryogenic Mission, only one instrument was on at a time for a sequence duration of one to three weeks.
 - ➤ Primary mirror operates between 5.6 K and 12 K.
- In the extended Warm Mission, only two bands of IRAC, 3.6 μ m and 4.5 μ m, will produce valid science data.
 - ➤ Primary mirror operates at ~26 K